

# MEMRECAM HX-3

High Speed Camera System

The MEMRECAM HX series:  
the world's most versatile family of  
high speed camera systems!

## MEMRECAM HX-3 FEATURES

CMOS Sensor: 2560 X 1920—  
all Active Pixels

Bit Depth: 12/10/8-bit  
(customer selectable)

Electronic Shutter:  
OPEN to  $<1\mu\text{sec}$

Variable Framing Profile:  
Test using a variety of frame  
rates, sequentially or in parallel.

Versatile Recording: Burst,  
multi-trigger, restart-trigger and  
image trigger.

A-EST Mode: High resolution  
timing and sync system to  
 $< 50$  nanoseconds.

Straddle Mode:  
Inter-frame time for  
PIV applications equals  
125 nanoseconds.

Dual Segment Recording:  
Simultaneously record to two  
distinct memory segments at two  
different imaging speeds.

Ultra-High Light Sensitivity

Ruggedized for Range Use



nac's MEMRECAM HX-3 offers an astounding 5 Mega Pixel resolution at up to 2,000 fps, Full HD resolution at up to 4,670 fps, 1 Mega Pixel resolution at up to 9,220 fps, and so much more! The HX-3 gives the user the best possible solutions: the highest resolutions available; the highest light sensitivity available; and ultra fast imaging.

The HX-3 is literally two cameras in one!

*When it comes to reliable, high-quality, high-speed camera systems,  
make the proven choice with nac and you'll see the visible difference!*

# MEMRECAM HX-3

## High Speed Camera System



MEMRECAM HX-3 High Resolution Mode		
Max Res (pixels)	2560 X 1920	
Optical Format	35.20 mm	
fps @ Max Res	2,000	
	Mono	Color
ISO Rating	10,000	2,500

MEMRECAM HX-3 High Speed Mode		
Max Res (pixels)	1280 X 960	
Optical Format	35.20 mm	
fps @ Max Res	7,690	
	Mono	Color
ISO Rating	40,000	10,000

Memory Option	16GB, 32GB, 64GB
Maximum fps	1,300,000

Imaging Formats	Max fps @ Format
High Def: 16 X 9	
1920 X 1080	4,670
1280 X 720	10,230
Other Formats	
4 Mega Pixel	2,400
2 Mega Pixel	4,740
1 Mega Pixel	9,220
XGA (1024 X 768)	11,780
768 X 576	20,230
VGA (640 X 480)	28,310
512 X 512	32,410
512 X 384	43,000
320 X 320	74,340
320 X 240	105,800
320 X 192	130,700
320 X 96	246,880
320 X 48	444,400
320 X 24	740,660

\* Note: Recording Time Depends on Memory Configuration, Resolution, Frame Rate and Image Bit Depth.  
 Recording Time (seconds) = [(Memory Configuration X 1024 X 1,000,000) / (Resolution/Frame)] / (Frames/Second)  
 Resolution/Frame (Bytes) = (Horizontal pixels X Vertical Pixels X Bit Depth/8)

nac Image Technology  
 MEMRECAM High Speed Camera Systems also Feature:

- Auto Exposure Control
- Adjustable Frame Rates
- Automatic Temperature Calibration
- Continuously Adjustable Resolution
- Ultra-Fast Gig-E Interface with DataLock
- Fast Download to USB 2.0 HDD
- Continuous Live Video Output
- Remote & Local Control—(no PC required)
- Memory Backup
- DRES—Dynamic Range Expansion Shutter
- Multiple Trigger Modes
- Memory Segmentation
- External Sync Recording
- IRIG-B Capture & Sync with Phase Shift
- Compact, Rugged Design - 5.5kg  
110W x 140H x 333D(mm)

Visit our website at  
[www.nacinc.com](http://www.nacinc.com)

Please Note: Specifications described above are preliminary and subject to change.



Contact Us in the Americas:

nac Image Technology  
 543 Country Club Drive, # B-534  
 Simi Valley, CA 93065  
 Tel: (800) 969-2711  
 E-mail: sales@nacinc.com

Contact Us in Europe:

nac Deutschland GmbH  
 Hedelfingerstr. 54-70  
 70327 Stuttgart, Germany  
 Tel: +49(0)711 2201 885  
 E-mail: rwestphal@nacinc.de

Contact Us in Asia:

nac Image Technology Inc.  
 2-11-3 Kita-Aoyama, Minato-ku  
 Tokyo 107-0061 Japan  
 Tel: +81 3 3796 7903  
 Email: nacinternational@camnac.co.jp